

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 8 only, South

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1958-59)

At a point 81 lks. S.89°50'E. of old cor. of 7, 8, 17 and 18. This point falling in smooth bed rock in bed of a little ravine, course E. I marked a cross "X" at exact cor. point for closing cor. to secs. 7 and 8, with 4 notches S. and 5 notches E. of cross (X)., from which

- A Chittem 8" dia., bears N.8°E., 57 lks. dist. mkd. T22S R11W S8 BT.
- A Vine Maple 4" dia., bears N.21°W., 62 lks. dist. mkd. T22S R11W S7 BT.
- An Alder 14" dia., bears S.88°E., 80 lks. dist. mkd. T22S R11W CC S7 & 8 BT.

Fd. and used in Elliott State Forest Bdy survey - 1939 or 1941 ? - DCSO records, Field book 123 Page 12

Survey by S.O. and H.J. Newhouse - For: Cape Arago Lumber Co. March 1957 - C.S. File 42/256 and M 1-54

Identify cor. from one remaining original BT:

- 14" Alder, now 36" S.88°E., 52.8 ft.

The location of this corner as it bears from the above described BT falls on a bed of smooth rock in a creek bottom. We make a diligent search for the original chisled X but conclude that due to the softness of the stone and constant erosion by water, that it is washed away. Mark a new X, 12" x 12" and drive an alum. tack in the center, from which bears

- 36" Alder S.88°E., 52.8 ft. mkd. S17 BT.
- 3/4" iron pipe S.55°W., 5.9 ft.

No other BTs available.

Fd. OK, August 1973 by Gibson, OSFD - M 51-28

Gary T. Smither for Scott Timber Co. Jan. - April 1997 - M 124-51

No remaining evidence of closing corner as established by Newhouse for Sections 7 & 8 in 1957.

Set Witness Corner - 2" aluminum cap on 5/8" x 30" iron rod in 60" Douglas Fir stump, on east edge of ridge running northeast. Witness corner is south of true line 3.74 ft. in center of said 60" D.Fir stump. Alum. cap bears S.88°53'40"E., 387.66 ft. from calculated position.

(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 201500

PRIMARY CORNER DESCRIPTION W.C. for Sec. Cor. for 7 & 8 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Aluminum cap marked:

T 22 S R 11 W
C C
S 7 | S 8
W C S 17
-
RLS 2485

New bearing trees -

17" Alder, S.70°E., 15.2 ft. to spike side center, scribed
"T22 R11 S17 BT"

36" Maple, S.4½°W., 23.1 ft. to spike side center, scribed
"T22 R11 S17 BT"

Note - 6 foot steel post set near monument.

Fd. Ok by Brent Bacon 2/2005 - M147-32