

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1964)

Set a stone 12x10x6 ins., 8" in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which
A Fir 6" dia., bears S.4°E., 59 lks. dist. mkd. ¼ S BT.
A Chittem 5" dia., bears N.42°E., 37 lks. dist. mkd. ¼ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Jan. 1964 - C.S. File 51/260-3

Original 12"x10"x6" stone, found in place with ¼ on West side, from which a:
6" Fir bears S.4°E., 59 lks.; now 22" dead Fir, face grown over.
5" Chittem bears N.42°E., 37 lks.; now 5" uproot, badly rotted.
Dry Creek, course N.20°E., West, 66.0 ft.; in place.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Bd. of Forestry ¼ S20 S29 1963 RS 359", 30" in ground, with orig. stone on N. side in small mound of rock, and from which a:
18" Cedar bears N.64°E., 85.5 ft. scribed ¼ S20 BT RS 359.
12 ft. high rock bluff, extending to 40 ft. high at 200 ft. South, bears S.13°W., 30.3 ft., scribed X B0.
Mouth of dry gully from West joins creek at N.38°W., 90 ft.
Set 4x4x72" white painted cedar post 2.0 ft. SW of corner pipe.
OSBF metal location poster on 25" Alder, N.77°E., 33.2 ft.

Fd. OK, August 1973 by Gibson, OSBF - M 34-56 and CS 55/101