

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 5 Page(s) 1868)

-----  
Set Fir post 3 ft. long, 4" dia., 18" in ground for the ¼ sec. corner bet. secs. 17 and 20, from which  
A Myrtle 6" dia., bears South, 32 lks. dist.  
A Hardhack 6" dia., bears N.89°W., 77 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1961-62)

-----  
At a point 37.60 chs., found a Myrtle 6" dia., bears South 32 lks. dist. which has been marked for one of the bearing trees to the old ¼ sec. cor. No trace of cor. could be found. Destroyed marks on tree.  
At 40 chains - Set a post, 3 ft. long and 3" sq., 2 ft. in ground for ¼ sec. cor. marked ¼ S. on N. face, from which  
A Fir 40" dia., bears S.86°W., 141 lks. dist. mkd. ¼ S BT  
A Myrtle 5" dia., bears N.39°E., 57 lks. dist. mkd. ¼ S BT

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - July 28, 1967 - M 34-56

-----  
Set OSBF I.P. with 3" bronze cap, 33" in ground, from which  
24" Myrtle S.75°W., 20.2 ft.  
34" Fir N.72°E., 56.0 ft. "RS 359"  
19" Fir N.15°E., 30.5 ft. with yellow metal location poster RS 359.  
4"x4"x72" white painted cedar post 1.2 ft. SE.

Fd. OK, August 1973 by Gibson, OSBF - M 51-28