

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 240540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by H.J. Newhouse, Hamilton, Hogue, Bennett and S.O. Newhouse - For: Cape Arago Lumber Co. - Aug. 1956/March 1957 C.S. File 42/256

At approximate Interior Cor. to sec. 8, We drive an I.P., from which bears:

10" Myrtle S.26°E., 5.0 ft. mkd. Int. S8.

48" Fir N.70°W., 30.0 ft. mkd. Int. S8.

This cor. is 25 ft. South of the top of a ridge running East and West.

Survey by Warren D. Hootman - For: Cape Arago Lumber Co. - Aug. 1958 - C.S. File 42/386 and M 12-47

Move this corner (Newhouse) North 9.0 ft. Use same BTs:

D.Fir 48" DBH bears N.87°W., 28.4 ft.

Myrtle 10" DBH bears S.10°30'E., 13.8 ft.

This corner lays South about 12 ft. from the top of E-W ridge.

Fd. OK, June 1962 by W. Hooman - RM 1-31

Gary T. Smither for Scott Timber Co. Jan. - April 1997 - M 124-51

Set - 3/4" Aluminum cap on 3/4" x 36" aluminum rod, cap marked:

RLS 2485

T 22 S R 11 W

C 1/4 S 8

1997

New bearing trees -

12" Alder, N.50°E., 12.7 ft. to spike side center, scribed "C¹/₄ S8 BT"

11" Alder, S.60°W., 23.1 ft. to spike side center, scribed "C¹/₄ S8 BT"

12" Fir, N.74°W., 20.7 ft. to spike side center, scribed "C¹/₄ S8 BT"

12" Fir, N.54°W., 26.7 ft. to spike side center, scribed "C¹/₄ S8 BT"

Hootman 1/2" inside diameter oron pipe bears west 9.1 ft.

Note - Set 6 ft. steel post near monument.