

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1955)

Set a post, 3 ft. long and 3" sq., 2 ft. in ground for 1/4 sec. cor. marked 1/4 S. on N. face, from which
A Maple 12" dia., bears N.57°W., 39 lks. dist. mkd. 1/4 S BT
A Cherry 12" dia., bears S.65°W., 9 lks. dist. mkd. 1/4 S BT

Survey by S.O. and H.J. Newhouse - For: Cape Arago Lumber Co. Aug. 1956/March 1957 - C.S. File 42/256

At a point 29.5 ft. West of a post set by Bill Styles on a survey for Evans Products Co. a discussion with Mr. Styles showed that he had run the North side of Sec. 8 and set the point by single proportionate measurement. Since out other sec. lines in Sec. 8 indicated no major irregularities, we accepted Mr. Styles location of the 1/4 cor. between Secs. 5 & 8 and
Set an Iron pipe from which bears
24" Maple N.45°W., 25.7 ft. mkd. 1/4 S5 BT.
18" Cedar S.13°E., 25.0 ft. mkd. 1/4 S8 BT.

Survey by Warren D. Hootman - For: Cape Arago Lumber Co. - Aug. 1958 - C.S. File 42/386 and M 12-47

Four ft. North of a post set by S.O. Newhouse, proportioned 1/4 cor., I make a careful search of the area for evidence of the orig. cor. Find remains of a Cherry tree on which there has been a face, but I can discern no scribing. I set off from the position of the Cherry tree, the record dist. and bearing and turn the bearing for the orig. Maple. At the record dist. and brg., I find a 24" Maple tree which is a Newhouse BT.; but has no visible scar.
Reset 1/4 corner at this point and use the Newhouse BT which are now:
R.Cedar 18" DBH bears S.4°00'E., 28.6 ft.
Maple 24" DBH bears N.57°00'W., 25.7 ft.
Corner lays on a steep West slope.

Survey by Richard Hintz - For: International Paper Co. - May 1980 - M 83-57

Found - 12" Maple, part of a cluster, bears N.47°W., 21.9 ft.
1/2" I.P. bears S.40°E., 2.83 ft.
(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set 1¼" Iron pipe with stamped brass cap, from which a New BT -50" Cedar bears S.7°E., 48.4 ft., scribed. Distance is taken to a 50d nail in the face of the BT.

Gary T. Smither for Scott Timber Co. Jan. - April 1997 - M 124-51

Found - 2½" Brass cap set by Hintz in 1980.
10" Maple in clump, N.47°W., 21.9 ft. fo spike in face.
54" Cedar, S.7°E., 48.4 ft. to spike in face.
New Bearing Trees -
15" Maple, N.13°W., 41.2 ft. scribed "T22 R11 ¼ S5 BT"
spike side center.
66" Cedar, S.10°W., 64.6 ft. scribed "T22 R11 ¼ S8 BT"
spike side center.
Note - set 6 ft. steel post near monument.

Fd. & used on Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20224-5)