TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 241500

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. for Sec. 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1960)

A stone in place, 12x7x4 ins. above ground which I mark ¼ on N. face for ¼ sec. cor. from which
A Fir 30" dia., bears N.80°W., 50 lks. dist. mkd. ¼ S BT.
A Cedar 12" dia., bears S.87°E., 110 lks. dist. mkd. ¼ S BT.

Survey by S.O. and H.J. Newhouse - For: Cape Arago Lumber Co. March 1957 - C.S. File 42/256 and M 1-54

Find no trace of original stone but find orig. BTs:
30" Fir now 60", N.80°W., 33.0 ft. mkd. ¼ S8 BT.
12" Cedar , 18" x 30", S.87°E., 73.0 ft. mkd. ¼ S17 BT.
Set Iron pipe for corner.

Survey by Warren D. Hootman - For: Cape Arago Lumber Co. - July 1958 - M 12-47 and C.S. File 42/386

Corner Report.
The S 1/4 corner of section 8 which is a pipe. The Cedar BT scribed by Newhouse is plain but the original D.Fir BT has slid into the canyon North of the corner about 400 ft. away.

Gary T. Smither for Scott Timber Co. Jan. - April 1997 - M 124-51

Set - 3¼" aluminum cap on 3/4" x 36" aluminum rod, cap mkd:

RLS 2485
T 22 S R 11 W
1/4 S 8
1997

New bearing trees -
10" Alder, WEST, 21.9 ft., to spike side center, bark scribed "¼ S8 BT"
13" Alder, S.28°E., 6.2 ft. to spike side center, bark scribed "¼ S8 BT"
13 " Alder, N.77°E., 22.5 ft. to spike side center, bark scribed "¼ S8 BT"
13" Alder, N.20°E., 12.9 ft. to spike side center, bark scribed "¼ S8 BT"
Note - Set 6 foot steel post near monument.