

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 276513

PRIMARY CORNER DESCRIPTION SW Corner Sec. 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1943)

I set a post 4 ft. long and 4" sq., 2 ft. in the ground for SW. cor. to Sec. 9, marked T22S S9 on NE.; R11W on SE.; and S8 on SW. faces with 4 notches on S. and E. edges, from which
A Fir 40" dia., bears N.89°E., 19 lks. dist. mkd. T22S R11W S9 BT.
An Alder 10" dia., bears N.62°W., 41 lks. dist. mkd. T22S R11W S8 BT.

Survey by Warren D. Hootman - For: Cape Arago Lumber Co. - Aug. 1958 - C.S. File 42/386 and M 12-47

Set 1" x 36" Pipe from the original BTs.
The Alder is present but face is rotted out, so scribe a new tree:
D.Fir 64" DBH S.14°30'W., 22.9 ft.

Fd. 1" Pipe and 2 stump BTs, Aug. 1971 by Gibson, OSBF - M 44-32 and C.S. File 55/233