

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 300246

PRIMARY CORNER DESCRIPTION West 1/4 Cor. for Sec. 28 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1950)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S. on W. face, from which
A Fir 10" dia., bears S.48°W., 87 lks. dist. mkd. ¼ S BT
A Fir 8" dia., bears S.23°E., 57 lks. dist. mkd. ¼ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Feb. 10, 1977 - C.S. File 58/31

Original 3"x3"x36" Post 24" in ground, missing. Foudn 1½" I.P. and cap in place, from which a:

10" Fir bears S.48°W., 87 lks.; now 37" in place, face closed.

8" Fir bears S.23°E., 57 lks.; now 33" in place, broke off at base, scribes ¼ S visible on broken off portion of tree, 1 ft. downhill.

Restoration by Gibson, 1966:

1½" x 36" G.I.P. with 3" bronze cap in mound of rock, in place, from which a

Creek 12", course NE, bears S.23°E., 78.0 ft. in place.

4"x4"x72" WPCP bears South 2.0 ft.; in place.

From above 1½" x 36" galv. I.P. scribed

A 27" Fir, bears N.08°E., 11.3 ft. to face, scribed ¼ S28 BT RS 359.