

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION C C for Secs. 17 and 20 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1962)

At a point 5.50 chs. S. of cor. to secs. 16, 17, 20, and 21,
At which point I set a stone 14x12x7 ins., 10" in the ground
for closing cor. to secs. 17 and 20 marked CC with 3 notches
on the S. and 4 notches on E. edges, from which
A Fir 30" dia., bears S.2°W., 215 lks. dist. mkd. T22S
R11W S20 BT.
A Cherry 20" dia., bears N.42°W., 118 lks. dist. mkd. T22S
R11W S17 BT.
A Fir 60" dia., bears N.86°E., 65 lks. dist. mkd. T22S
R11W CC S17 & 20 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - E. Driver, transitman - July 1960 - C.S. File 42/403-8

Original stone 14"x12"x7", found badly weathered stone in place, no trace of notches, from which a:
30" Fir bears S.2°W., 215 lks.; now a rotted stub.
20" Cherry bears N.42°W., 118 lks.; missing.
60" Fir bears N.86°E., 65 lks.; now 73", portion of face exposed by unknown party, scribe 1 visible, remainder unexposed.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Bd. of Forestry T22S R11W S17 S20 S21 CC 1960 RS 359", 14" in ground, down to solid rock, in mound of stone, and from which
14" Fir bears S.41½°W., 16.3 ft. scribed T22S R11W S20 CC BT.
25" Fir bears N.17°E., 6.7 ft. scribed RS 359.
OSBF metal location poster on 14" Fir BT.
Corner falls on top of spur ridge sloping North.

Fd. OK, Aug. 1973 by Gibson, OSBF - M 51-28