

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 300406

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16 and 21 only (West)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1945)

Set a post 4 ft. long and 4" sq., 2 ft. in the ground for cor. to secs. 16, 17, 20 and 21, marked T22S S16 on NE.; R11W S21 on SE.; S20 on the SW.; and S17 on NW. faces, with 3 notches on S. and 4 notches on E. edges, from which

- A Fir 40" dia., bears N.19°E., 70 lks. dist. mkd. T22S R11W S16 BT.
- A Maple 10" dia., bears S.22°E., 64 lks. dist. mkd. T22S R11W S21 BT.
- A Chittem 4" dia., bears S.23°W., 108 lks. dist. mkd. T22S R11W S20 BT.
- A Hemlock 24" dia., bears N.8°W., 117 lks. dist. mkd. T22S R11W S17 BT.

Sec. Cor. Fd., OSBF P/C, 3 BTs - July 1967, A. Gibson, OSBF -M 34-56

Sec. Cor. Fd., OSBF P/C, 3 orig. BTs and 1 new BT - by Gibson, Aug. 1973 - M 51-28