

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 300446

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 16 only (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1944)

A stone in place 24x16x16 ins., above ground which I marked with a cross (X) at exact cor. point and ¼ on W. face for ¼ sec. cor., from which

A Fir 36" dia., bears S.80°E., 135 lks. dist. mkd. ¼ S BT.

An Alder 4" dia., bears S.49°W., 89 lks. dist. mk.d ¼ S BT

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: E.D. Kucera - Nov. 6, 1968 - C.S. File 55/101-9

Orig. 24x16x16" sandstone, in place, good condition, X and ¼ on W. face., from which

36" Fir bears S.80°E., 135 lks.; now 60" stump, in place, used for guyline stump, notched and spikes remain, no face visible.

4" Alder bears S.49°W., 89 lks.; now missing.

Set 4x4x72" white painted cedar post 1.0 ft. SW of corner stone, from which

23" Fir bears S.12°E., 16.8 ft. to face, scribed ¼ S16 BT

17" Fir bears S.59°E., 9.4 ft. to face, scribed ¼ S16 BT

RS 359.

OSBF metal location poster on 17" Fir BT S.59°E., 9.4 ft.

Fd. OK, Aug. 1973 by Gibson, OSBF - M 51-28

Fd. Ok by B. Bacon, Oct. 2004 - M145-62