

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION C.C. for Secs. 8 and 17 (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1960)

I set a stone 18x16x12 ins. in the ground for closing cor. to secs. 8 and 17, marked CC with 4 notches on S. and E. edges, from which

- A Fir 40" dia., bears S.17°W., 41 lks. dist. mkd. T22S R11W S17 BT.
- A Fir 30" dia., bears N.26°W., 41 lks. dist. mkd. T22S R11W S8 BT.
- A Fir 36" dia., bears S.35°E., 66 lks. dist. mkd. T22S R11W S8 & 17 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: David Kucera - Dec. 3, 1968 - C.S. File 55/101-8

Original stone 18x16x12", now missing, logged area, from which a:

- 40" Fir bears S.17°W., 41 lks.; now a 51" stump, face closed.
- 30" Fir bears N.26°W., 41 lks.; now a 53" stump, face closed.
- 36" Fir bears S.35°E., 66 lks.; now a 42" stump, exposed scribe 8.

Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Bd. of Forestry T22S CC S8 S17 R11W S16 1968 RS 359", 34" in ground, from which

- 13" Maple bears S.39°W., 12.7 ft. scribed T22S R11W S17 BT
- 53" Fir stump, orig., bears N.26°W., 27.1 ft. scribed BT RS 359.
- 4x5x1½ ft. high rock outcrop bears N.41°E*, 4.0 ft marked with a 4" X BO. - *bearing corrected 2/13/2015 JC DCSO
- Set 4x4x72" white painted cedar post, 1.0 ft. S. of corner pipe.
- OSBF metal location poster on 13" Maple BT S.39°W., 12.7 ft.
- Also BLM posters on the three original BTs.

Fd. OK, Aug. 1973 by Gibson, OSBF - M 51-28

Gary T. Smither for Scott Timber Co. Jan. - April 1997 - M 124-51

Found - 3" Bronze disk set by Gibson in 1968.
53" Fir stump, N.26°W., 41 lks. with tag.
42" Fir stump, S.35°E., 66 lks. axe mark in face.
(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION C.C. for Secs. 8 and 17 (East)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

51" Fir stump, S.17°W., 41 lks. with tag.
New bearing trees -
9" Maple, S.60°W., 10.0 ft. scribed "T22 R11 ¼ S17
BT" spike side center.
16" Fir, S.56°E., 45.1 ft. scribed "T22 R11 ¼ S16 BT"
spike side center.
Note - 6 foot steel post set near monument.

Fd. Ok by B. Bacon, Oct. 2004 - M145-62

Brent Bacon - For: Menasha Forest Products - 2/2005 - M147-32

Found - 1 1/2" iron pipe with 3" brass cap mkd "T22S CC S8
S17 S16 R11W 1969 RS359"
21" fir, S.52°E., 45.3' to spike, healed face (rec
S.56°E., 45.1')
46" fir stump, S.33°E., 43.1', chopped open face
(rec. 43.6')
48" fir stump, S.18°W. 26.3', healed face (rec.
27.1')
11" maple, S.60°W., 10.0' to spike, healed face.
50" fir stump, N.25°W., 26.9'.

Jerry Estabrook - For: State of Oregon, Department of
Forestry - January 2015 - M169-4

Found - A 1½" iron pipe with 3" brass cap mkd "T22S CC S8
S17 S16 R11W 1968 RS359" PER CS 55/101-8
A 30" fir with healed face and YMLP bears S.52°E.,
45.3'.
A 46" original fir, now a stump with YMLP bears
S.33°E., 43.1'.
A 48" original fir, now a stump with YMLP bears
S.18°W., 26.3'.
A 12" maple with healed face and YMLP bears S.60°W.,
10.0'.
A 50" original fir stump with YMLP bears N.25°W.,
26.9'.
A Rock outcrop marked "X BC" bears N.41°E., 4,0',
The record bearing for this BO was N.41°E., per
CS 55/101-8
A steel fence post bears South 0.5'.
New BO - An orange carsonite post East 3.2'.
Lat. and Long. Per CARMEN ETREX hand held GPS:
N: 43°39'45.8" W: 124°01'43.4"