

PRIMARY CORNER DESCRIPTION NW Cor. Section 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1938)

Set a stone 10x8x7 ins., 7" in ground for cor. to secs. 16 & 17, marked with 4 notches on S. and E. edges, from which
A Fir 30" dia., bears S.21°E., 25 lks. dist. mkd. T22S R11W S16 BT.
A Fir 16" dia., bears S.52°W., 6 lks. dist. mkd. T22S R11W S17 BT.
A Fir 20" dia., bears N.54°W., 11 lks. dist. mkd. T22S R11W S16 & 17 BT.

Elliott State Forest Boundary Survey - L. Beyers and E. Lough - 1941 - (DCSO Field Book 120 Page 135)

Found a stone with 2 notches and 3 BTs as described. Set 4"x4"x3 ft. Cedar post for NW cor. S.16.

Survey by Warren D. Hootman - For: Cape Arago Lumber Co. - Aug. 1958 - C.S. File 42/386 and M 12-47

Found - 4" x 4" white post, 4 ft. North.
All orig. BTs. The BT listed as a 30" D.Fir S.21°E., 25 lks. is presently 50" D.Fir with no visible face.
20" D.Fir snag with a grown over face sits on bearing at the base of the larger tree.
BT, N.54°W., 11 lks. is down and a tree has fallen over the corner position.
Also find a tree with an obvious face scar healed over, S.40°00'E., 15.2 ft.
Mark a 60" D.Fir N.8°30'W., 34.0 ft.
This cor. lays on a West slope at the NE. edge of the clear area mentioned before, about 50 ft. North and 40'E. of a draw going NW.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: E.D. Kucera - Dec. 16, 1968 - C.S. File 55/101-7

Orig. stone 10x8x7", now missing. Logged area, from which a:
30" Fir bears S.21°E., 25 lks.; now missing.
16" Fir bears S.52°W., 6 lks.; now a 16"x10 ft. stub that was growing from a root on the N. side of a 50" Fir stump, bearing S.30°W., 6.5 ft., exposed scribes 2S.
20" Fir bears N.54°W., 11 lks.; now missing.
(Cont. Next Page)

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 16

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Restoration by Hootman, 1958 (See above record)
 Set 1½" x 36" galv. Iron pipe with 3" bronze cap mkd. "Ore. St. Bd. of Forestry" S9 S8 T22S R11W S16 1968 RS 359", 34" in ground, and from which a:
 48" Fir stump bears N.12°W., 35.6 ft. scribed T22S R11W S9 BT.
 44" Fir stump bears S.69°W., 15.7 ft. scribed T22S R11W S8 BT.
 No trees available for BTs in section 16.
 Found 4"x4" white post, missing, 4 ft. N. & all orig BTs Mkd. 60" D.Fir N.8½°W., 34.0 ft.; now missing, edge of slide out.
 Set 4x4x72" White painted cedar post 1.0 ft SE of corner pipe OSBF metal location poster on 48" Fir stump, N.12¼°W. 35.6 ft
 Also BLM poster on the orig. 16" Fir, S.52°W., 6 lks.

Fd. OK, August 1971 by Gibson, OSBF - M 44-32 and CS 55/233

Brent Bacon - For: Menasha Forest Products - 10/2004 - M145-62

Found - 16" Fir snag, S.52°W., 4.0' visible scribe "2S"
 45" rotten fir stump, S.69°W., 15.7 ft. to face, no marks.
 49" rotten fir stump, N.12°W., 35.6 ft. to face, no marks.
 Set - 1½"x30" iron pipe with 2" brass cap, mkd: "T22S R11W S9 S8 S16 2004 LS 2869"
 18" Alder, N.63°E., 21.6', bark scribed "T22S R11W S16 BT"
 35" Maple S.79°W., 94.7', scribed "T22S R11W S8 BT"
 "OX" chiseled in rock face, S.57°E., 1.2' to center of "X"

Jerry Estabrook - For: State of Oregon, Department of Forestry - January 2015 - M169-4

Found - A 1½"x36" iron pipe with 3" brass cap mkd "T22S R11W ¼ S9 1975" PER CS 58/56, laying on top of ground. Reset monument from found BTS.
 A 15" rotten fir stump with no visible marks bears N.55°30'E., 18.5'.
 A 32" rotten fir stump with visible scribe in opened face bears N.33°W., 21.5'.
 NEW BTs- A 10" Fir, face scribed "S¼ S9 BT" with MAG NAIL and washer stamped "LS2703" in bottom of face and with x-chop and YMLP at breast height bears N.28°E., 10.25' to a spike at side center.

continued next page

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 300513

PRIMARY CORNER DESCRIPTION NW Cor. Section 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A 10" Fir, face scribed "S¼ S9 BT" with MAG NAIL and washer stamped "LS2703" in bottom of face and with x-chop and YMLP at breast height bears N.26°W., 13.53' to a spike at side center.
New BOs- An orange carsonite post bears north 2.0'.
 An orange carsonite post bears west 2.0'.
Lat. and Long. Per GARMEN ETREX hand held GPS:
N: 43°39'53.8" W: 124°01'10.7"