

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 300520

PRIMARY CORNER DESCRIPTION So. 1/16 Cor. betw. Secs. 8 and 9

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Aug. 13, 1971 - M 44-32

Established. obliterated Hootman's 1/16th corner, S.23°08'E., 58.41 ft. as per agreement with him.
Set OSBF I.P. and 3" bronze cap, in ground.
31" Fir stump N.59½°W., 22.1 ft. "RS 359" and yellow metal location poster.
"X" on 8 ft. x 20 ft. rock face, in slide out draw, N.21½°E., 43.4 ft. 9" X BO.
4"x4"x72" white painted cedar post N.54°E., 3.6 ft.

Gary T. Smither for Scott Timber Co. Jan. - April 1997 - M 124-51

Found - 3" Bronze disk set by Gibson 1971.
"X" on rock, N.21½°E., 43.4 ft.
31" Fir stump, N.59½°W., 22.1 ft. visible scribe.
New bearing trees -
8" Alder, S.20°W., 15.4 ft. bark scribe "S 1/16 S8 BT" spike side center.
7" Alder, N.54°E., 6.1 ft. bark scribe "S 1/16 S9 BT" spike side center.
Note - 6 foot steel post set near monument.