

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1943)

Set a post, 3 ft. long and 3" sq., 2 ft. in the ground for ¼ sec. cor. mkd. ¼ S. on W. face, from which
A Cherry 4" dia., bears N.73°E., 6 lks. dist. mkd. ¼ S BT.
A Cherry 5" dia., bears S.74°W., 15 lks. dist. mkd. ¼ S BT

Survey by Warren D. Hootman - For: Cape Arago Lumber Co. - Aug. 1958 - C.S. File 42/386 and M 12-47

Set a pipe, from which a:
D.Fir 20" DBH bears N.64°E., 28.2 ft.
D.Fir 22" DBH bears S.48°W., 2.0 ft.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Dated Oct. 1971 - C.S. File 55/233-7

No evidence of original corner found.
Reestablishment by Hootman:
I.P., missing, from which a:
20" Fir bears N.64°E., 28.2 ft.; now 21", scribe marks visible in partially closed face.
22" Fir bears S.48°W., 2.0 ft.; now 26", scribes 1S visible in partially closed face.
Set I.P. with 3" bronze cap mkd. "Ore. St. Bd. of Forestry ¼ S8 S9 1971 RS 359", 34" in ground and from which a:
27" Fir bears S.3½°W., 92.7 ft. to face, scribed ¼ S8 BT RS 359.
21" Fir bears N.34½°E., 73.5 ft. to face, scribed ¼ S9 BT
Set 4"x4"x72" white painted cedar post 3.5 ft. N.21°E., of corner pipe.
OSBF metal location poster on 21" Fir BT, N.34½°E., 73.5'.
Also poster on 26" Fir BT, S.48°W., 2.0 ft. (Hootman BT)

Fd. OK, June 1975 by R. Stuntzner - M 57-54

Gary T. Smither for Scott Timber Co. Jan. - April 1997 - M 124-51

Found - 3" Bronze disk set by Gibson in 1971.
20" Fir stump, N.64°E., 28.2 ft. healed face
30" Fir stump, S.48°W., 2.0 ft. with tags
38" Fir, S.3½°W., 92.7 ft. healed face

(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New bearing trees -
8" Fir, S.72°E., 22.6 ft. scribed "T22 R11 ¼ S9 BT" spike
side center.
8" Fir, S.18°W., 15.7 ft. scribed "T22 R11 ¼ S8 BT" spike
side center.
Note - 6 foot steel post set near monument.