

PRIMARY CORNER DESCRIPTION Sec. Cor. for 4, 5, 8 and 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1941)

Set a post, 4 ft. long and 4" sq., 2 ft. in the ground for cor. to secs. 4, 5, 8 and 9, marked T22S S4 on NE.; R11W S9 on SE.; S8 on SW.; and S5 on NW. faces with 5 notches on S. and 4 notches on E. edges, from which

- A Fir 36" dia., bears N.48°E., 66 lks. dist. mkd. T22S R11W S4 BT.
- A Fir 36" dia., bears S.58°E., 20 lks. dist. mkd. T22S R11W S9 BT.
- A Fir 24" dia., bears S.57°W., 45 lks. dist. mkd. T22S R11W S8 BT.
- A Cedar 24" dia., bears N.36°W., 23 lks. dist. mkd. T22S R11W S5 BT.

Elliott State Forest Boundary Survey - L. Beyers and E. Lough - 1941 - (DCSO Field Book 120 Page 121)

Found 3 BTs as described. Set cor.

Survey by Arnold G. Gibson - For: Oregon St Board of Forestry - Wit: Lloyd D. Smith - 9/29/1970 - C.S. File 55/154-9

Orig. post, missing. Found Elliott 4"x4"x4 ft. white post in mound of rock, in place, from which a

- 36" Fir bears N.48°E.; 66 lks.; missing.
- 36" Fir bears S.58°E., 20 lks.; now 20" x 12 ft. rotted windfall.
- 24" Fir bears S.57°W., 45 lks.; now 31" windfall, downhill, out of place, exposed scribes T2 11 (face N.83°W., 24.6 ft.)

Restoration by Elliott Forest Survey, 1941:

Cedar post.

Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Bd. of Forestry T22S R11W S4 S5 S8 S9 1970 RS 359", 32" in ground, in Elliott post hole, with Elliott post laying alongside, in mound of rock, and from which a:

- 24" Fir bears N.6°W., 116.5 ft. to face, scribed T22SR11W S5 BT RS359.
- 42" Fir bears S.80°E., 38.7 ft. to face, scribed T22S R11W S9 BT.
- 43" Fir bears N.32°E., 41.6 ft. to face, "T22S R11W S4 BT"

Set 4"x4"x72" white painted cedar post 2.0 ft. S.45°W. of corner pipe. OSBF metal location poster on 24" Fir BT, N.6°W.

PRIMARY CORNER DESCRIPTION Sec. cor. for 4, 5, 8 and 9

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

Fd. OK, June 1975 by R. Stuntzner - M 57-54
 Fd. OK, Nov. 1978 by T. Hoesly - M 74-65
 Fd. OK, May 1980 by R. Hintz - M 83-57

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20223-4)

 From the cor. of secs. 4, 5, 8, & 9, remonumented from original evidence no longer in existence by Gibson, in 1970, utilized by Hosley, in 1978, and further utilized by Hintz, in 1980, determined at record distance from the remains of bearing trees mkd. by Gibson:
 A fir stump, 43" diam., bears N.30 3/4°E., 65½ lks., with healed blaze. (Record, 63 lks. to face.)
 A fir stump, 42" diam., bears S.81½°E., 61½ lks., with healed blaze. (Record, 58½ lks. to face.)
 At the corner point
 Set a brass tablet, 3¼" diam., 3½ in. stem, in drill hole in solid rock, with top mkd.

T22S	R11W
S 5	S 4
S 8	S 9
1992	

from which a new bearing tree
 A fir, 7" diam., bears N.75¾°W., 33½ lks., mkd. T22S R11W S5 BT.
 No other suitable accessories available.

Jerry Estabrook - Crew: Pat Coy, John Rondeau & Ray Banks - 5/24/2019 - C.S. File 65/102-65

 FOUND - A 3¼" brass tablet marked "T22S R11W S4 S5 S8 S9 1992" in solid rock.
 A 43" Fir stump with healed face and tag bears N.30°45'E 43.23'.
 A 42" Fir stump with healed face and tag bears S.81°30'E., 40.59'.
 A 17" Fir stump with healed face and tag bears N.75°45'W 22.11'.
 New - A 13" alder, bark scribed "SW S4 BT" with x-chop and tag bears N.25°E., 32.20' to a spike at side center.
 A 9" alder, bark scribed "SW S4 BT" with x-chop and tag bears N.62°E. 18.9' to a spike at side center
 LAT. and LONG. per GARMIN ETREX HAND HELD GPS
 N: 43°40'41.6" W:124°01'46.6"
 Declination used on hand compass 18° EAST