

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1940)

Bluff of rock, 15 ft. long and 4 ft. high, course N. & S. I marked a cross (X) at exact cor. point on face of bluff with ¼ N. of cross (X) for ¼ sec. cor. from which
A Spruce 8" dia., bears S.88°W., 27 lks. dist. mkd. ¼ S BT
A Fir 24" dia., bears S.1°E., 46 lks. dist. mkd. ¼ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: Lloyd D. Smith - Dec. 18, 1970 - C.S. File 55/154-10

Orig. bluff of rock 15'x4' with cross X at exact corner point; bluff in place ¼ S visible, from which a
8" Spruce bears S.88°W., 27 lks.; now 24" rotted stump, backcast S4 S visible.
24" Fir bears S.1°E., 46 lks.; now 56", face grown over, in place.
Chiseled 4" X on orig. rock bluff at exact cor. point, from which
15" Fir bears S.2¼°W., 25.0 ft. to face; scribed S5 BT.
20" Fir bears N.17½°E., 49.9 ft. to face, scribed ¼ S4 BT RS 359.
Set 4"x4"x72" white painted cedar post 2.2 ft. W. of corner stone.
OSBF metal location poster on 15" Fir, S.2¼°W, 25.0 ft.

Fd. OK, Nov. 1978 by T. Hoesly - M 74-65

Fd. OK, May 1980 by R. Hintz - M 83-57

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20222-3)

From the ¼ sec. cor. of secs. 4 & 5, perpetuated from original evidence by Gibson, in 1970, utilized by Hosley, in 1978, and further utilized by Hintz, in 1980; monumented with an X chiseled on rock bluff, 15 X 4 ft., from which a bearing tree mkd. by Gibson:
A fir, 17" diam., bears S.2¼°E., 38½ lks., w/healed blaze. and a bearing tree not of known record
A fir, 21" diam., bears S.82½°E., 33½ lks., with scribe marks ¼ S4 BT visible on partially healed blaze.
continued next page

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point
Set a brass tablet, 3¼" diam., 3½ in. stem, in drill hole in
solid rock, with top mkd.

T22S R11W
1/4
S 5 | S 4
1992