

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 329100

PRIMARY CORNER DESCRIPTION A.P. on So. bdy. Sec. 33

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1879)

Set an iron rod, 4 ft. long, 1" dia., 2 ft. in the ground for cor. to secs. 4 and 5 marked with 4 notches on E. and 2 notches on W. sides, from which
A burnt Fir 50" dia., bears S.8°E., 119 lks. dist. mkd. T23S R11W S4 BT.
An Alder 10" dia., bears S.75°W., 27 lks. dist. mkd. T23S R11W S5 BT.
A Myrtle 4" dia., bears N.58°W., 14 lks. dist. mkd. T23S R11W S4 & 5 BT.

GLO survey by Albert N. Gould, Deputy Surveyor, under Contract #762, dated July 12, 1905 - (DCSO records Vol. 5 Page(s) 1977)

Cor. of secs. 4 & 5 which is an iron rod, 1" dia., 12" high, witnessed as described by the Surveyor General which said witnesses I marked A.P BT.

Survey for Elliott State Forest Boundary - 1933-34 - DCSO Field Book 124 Page 8

Found 1894 Whipple corner to sec. 4 & 5 on N. bdy. of Tsp., which is a 1" Iron rod, from which
A 20" Alder bears S.75°W., 18 ft.
A clump of Myrtle bears N.60°W., 9 ft.
(Gould A.P.)

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Sept. 11, 1969 - M 38-53

AP section 5 (Orig. cor. 4 & 5 found, OSBF P/C, 2 orig. BTs, 2 new BTs.