

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION So. 1/4 Corner for Sec. 9 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Restored by W. Metcalf - June 5, 1975 - C.S. File 58/56

Set OSBF 1½" x 36" galv. I.P. and 3" bronze cap, 35" in ground in mound of rock, from which
32" Fir N.33°W., 21.5 ft. with yellow metal location poster, "RS 359".
15" Fir N.55½°E., 18.5 ft. with yellow metal location poster.
4"x4"x72" white painted cedar post, N.67½°E., 8.0 ft.
1941 Elliott survey post bears S.77½°W., 2.9 ft.

Jerry Estabrook - For: State of Oregon, Department of Forestry - January 2015 - M169-4

Found - A 1½" iron pipe with 2" brass cap mkd "T22S R11W S9 S8 S16 2004 LS2869 per M145-62
A 20" alder with bark scribe and YMLP bears N.63°E., 21.6'
A 16" orig. now rotten fir snag with chop mark in face bears S.52°W., 4.0'.
A 45" rotten fir stump with no visible marks bears S.69°W., 15.7'.
A 43" maple with possible bark scribe and YMLP bears S.79°W., 94.7'.
A 49" rotten fir stump with tag on top bears N.12°W., 35.6'.
A rock face with OX mark bears S.57°E., 1.2'.
New BO - An orange carsonite post set alongside monument.
Lat. and Long. Per GARMEN ETREX hand held GPS:
N: 43°39'53.1" W: 124°01'42.9"