

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1942)

Set a post, 3 ft. long and 3" sq., 2 ft. in the ground for ¼ sec. cor. marked ¼ S. on N. face, from which
A Cherry 4" dia., bears N.2°E., 27 lks. dist. mkd. ¼ S BT
A Fir 48" dia., bears S.65°W., 44 lks. dist. mkd. ¼ S BT.

Elliott State Forest Boundary Survey - L. Beyers and E. Lough - 1941 - (DCSO Field Book 120 Page 117-118)

Found a 54" Fir with several axe marks and blaze similar to BT. No other tree to answer near. From which
Set - 4"x4"x3' Cedar post N.63°E. 44 lks. for ¼ cor. 4/9

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - by Elbert Drive - Filed Feb. 24, 1958 - C.S. File 42/340-1

Original post, now missing. Found rotted stake point in place and 4x4x8" white painted cedar post 6" from stake hole.
4" Cherry bears N.2°E., 27 lks.; now missing.
48" Fir bears S.65°W., 44 lks.; now 56", uncovered scribes S 4, remainder unexposed.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Oregon State Board of Forestry ¼ S4 S9 1958 RS 359", 33" in ground, and from which a:
16" Fir bears N.54°E., 10.0 ft. scribed ¼ S4 BT.
12" Fir bears S.61°E., 6.5 ft. scribed RS 359.
Reset 4x4x8" white painted cedar post 1.5 ft. SW. of pipe.
OSBF metal location poster on 8" Fir S.31°W., 7.0 ft.

Fd. OK, June 1975 by R. Stuntzner - M 57-54

Fd. OK, Nov. 1978 by T. Hoesly - M 74-65

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20220-1)

From the 1/4 sec. cor of secs. 4 & 9, remonumented by Gibson, in 1958, and further perpetuated by Gibson in 1970, utilized by Gibson in 1971, utilized by Stuntzner in 1975, and further utilized by Hosley, in 1978; monumented with an iron post, 1½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd. continued next page

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

T22S R11W
1/4 S 4
 S 9
 1958
 359

from which the remains of an original bearing tree
A fir stump, 59" diam., bears S.65°W., 44 lks., with axe
marks visible on healed blaze.
and remains of bearing trees mkd. by Gibson in 1958
A fir, 32" diam., bears N.54°E., 17½ lks., with healed
blaze.
A fir stub, size indeterminate, bears S.54°E., 10½ lks.,
no marks visible.
and a new bearing tree
A fir, 16" diam., bears S.17½°E., 43½ lks., mkd. ¼ S9 BT.