

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 340640

PRIMARY CORNER DESCRIPTION Center 1/4 cor. Sec. 4

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor,  
& Richard Sanford, Surveying Technician, under Group #1644,  
surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s)  
20227-8)

-----  
Point for the center ¼ sec. cor. of sec. 4, at intersection  
with the E. and W. centerline.

Set a stainless steel post, 28" long, 2½" diam., 24" in the  
ground, with brass cap mkd. T22S R11W

C 1/4 S 4  
1992

from which

A fir, 11" diam. bears N.29 3/4°E. 192 lks. mkd. C ¼ S4 BT

A fir, 19" diam., bears N.30¼°W., 136 lks., mkd. C ¼ S4 BT

Deposit a white "DEEP-1" magnetic marker at base of stainless  
steel post.

Corner is located on top of ridge, bears N.35°E. and S.35°W.

-----  
Tony Hostetter - For: Menasha Log Co. - Oct. 2014 - C.S. File  
65/86-35

FOUND - 1992 BLM brass cap

New - 12" Fir, scribed "S4 C¼ BT" BT tag; bears  
N.55°44'E., 30.8 feet to spike.

10" Fir, scribed "S4 C¼ BT", BT tag; bears  
S.28°01'E., 21.0 feet to spike.

10" Fir, scribed "S4 C¼ BT", BT tag; bears  
S.24°29"W., 10.2 feet to spike.

12" Fir, scribed "S4 C¼ BT", BT tag; bears  
N.06°42'W., 4.1 feet to spike.