

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 344500

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 16 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1937)

Set a post 3 ft. long and 3" sq. for ¼ sec. cor. marked ¼ S. on N. face, from which

A Cherry 3" dia., bears N.33°E., 12 lks. dist. mkd. ¼ S BT.

A Willow 4" dia., bears S.52°W., 50 lks. dist. mkd. ¼ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Jan. 27, 1971 - M 42-26

Set OSBF 1½" x 36" galv. iron pipe with 3" bronze cap, from which

24" Fir S.66°E., 29.0 ft. "RS 359" with yellow metal location poster.

26" Fir S.51°W., 37.2 ft.

4"x4"x72" white painted cedar post, East 1.0 ft.

1941 Elliott Survey post, East 5.7 ft.

Jerry Estabrook - For: State of Oregon, Department of Forestry - January 2015 - M169-4

FOUND - A 24" rotten fir stump with no visible marks S.66°E., 29.0'. Found old YMLP on ground and placed it back on BT.

A 26" rotten fir stump with visible scribe in opened face bears S.51°W., 37.2'.

New - A 5/8"x30" Iron rod with plastic cap mkd "ESTABROOK LS2703".

A 14" fir, face scribed "N¼ S16 BT" with MAG NAIL and washer stamped "LS2703" and with X-chop and YMLP at breast height bears S.75°E., 6.10' to a spike at side center.

An 11" fir, face scribed "N¼ S16 BT" with MAG NAIL and washer stamped "LS2703" and with X-chop and YMLP at breast height bears S.54°W., 5.85' to a spike at side center.

An orange carsonite post bears south 2.0'.

An orange carsonite post bears west 2.0'.

Lat. and Long. Per GARMEN ETREX hand held GPS:

N: 43°39'54.0" W: 124°01'08.0"

