

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 367100

PRIMARY CORNER DESCRIPTION No. Sec. cor. for 4 & 5 only, T23-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Albert N. Gould, Deputy Surveyor, under Contract #762, dated July 12, 1905 - (DCSO records C.S. File 62/35-15 H)

-----  
At a point 13.08 chs. N.89°52'W. of the CC to secs. 33 & 34, Set a Fir limb post, 3 ft. long, 4" sq., 24" in the ground for closing cor. to secs. 4 & 5, marked CC T23S R11W on S.; S4 on E.; and S5 on W. faces, with 2 grooves on W. and 4 grooves on E. faces, from which

A Fir 12" dia., bears S.61°E., 46 lks. dist. mkd. T23S R11W S4 BT.

A Fir 10" dia., bears S.25°W., 49 lks. dist. mkd. T23S R11W S5 BT.

Survey for Elliott State Forest Boundary - 1933-34 - DCSO records, Field Book 124 Page 11

-----  
Found corner to secs. 4 & 5, a Fir post which was still partly intact and bearing trees.

Set 4" x 4" x 4' Fir post, from which

A Fir 18" dia., bears S.61°E., 46 ft.

A Fir 16" dia., bears S.25°W., 49 ft.