

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1929)

Set a stone 12x10x8 ins., 8" in the ground for cor. to secs. 15, 16, 21 and 22, marked with 3 notches on the S. and E. edges, from which

- A Fir 4" dia., bears N.25°E., 26 lks. dist. mkd. T22S R11W S15 BT.
- A Fir 6" dia., bears S.60°E., 4 lks. dist. mkd. T22S R11W S22 BT.
- A Fir 8" dia., bears S.69°W., 15 lks. dist. mkd. T22S R11W S21 BT.
- A Fir 7" dia., bears N.25°W., 11 lks. dist. mkd. T22S R11W S16 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: L. Smith and D. Brown - July 15, 1970 - C.S. File 55/154-7

Found orig. 12"x10"x8" stone, in place, badly decomposed, from which a:

- 4" Fir bears N.25°E., 26 lks.; now 17" stump, chopped into, no scribes visible.
- 6" Fir bears S.60°E., 4 lks.; now 21" x 12 ft. stub, with 12"x6"x10' section split out from base of chopping to top of stub.
- 8" Fir bears S.69°W., 15 lks.; now 21", face grown over.
- 7" Fir bears N.25°W., 11 lks.; now 19" x 11 ft. stump, scribe "B" visible.

Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Bd. of Forestry T22S R11W S15 S16 S21 S22 1970 RS 359", 24" in ground with orig. stone alongside, in mound of rock, and from which a:

- 17" Fir, orig., bears S.69°W., 9.9 ft. scribed "RS 359".
- 10" Fir bears S.3°E., 48.8 ft. to face, scribed T22S R11W S15 BT.
- 24" Fir bears S.62°E., 43.3 ft. to face, scribed T22S R11W S22 BT.

Set 4"x4"x72" white painted cedar post 2.8 ft. N.28°E. of corner pipe.

OSBF metal location poster on 17" Fir, S.69°W., 9.9 ft.

Fd. OK, Aug. 1973, by OSBF - M 51-28

continued next page

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Jerry Estabrook - For: Oregon Dept. of Forestry - Feb. 2017 - M173-9

Found - A 1½" iron pipe with 3" brass cap mkd "T22S R11W S15 S16 S21 S22 1970 RS359" per CS 55/154.
An orig. fir, now rotten snag with no visible marks bears S.60°E., 2.64' to face.
An orig. 36" Fir with healed face and new tag bears S.69°W., 9.9'.
An orig. Fir, now rotten stump with no visible marks bears N.25°W., 7.26'.
A 33" Fir with healed face and new tag bears S.62°E., 43.3' to face.
New BTs- A 36" Fir face scribed "SW S15 BT" with mag nail and washer stamped "LS2703" in bottom of face and with x-chop and YMLP at breast height bears N.01°E., 50.7' to a spike at side center.
A 25" Fir face scribed "NW S22 BT" with mag nail and washer stamped "LS2703" in bottom of face and with x-chop and YMLP at breast height bears S.84°E., 48.3' to a spike at side center.
New BO - An orange carsonite post bears west 2.0'.