

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1929)

Set a post, 3 ft. long and 3" sq., 2 ft. in the ground for ¼ sec. cor. marked ¼ S. on W. face, from which
A Fir 12" dia., bears N.52°W., 4 lks. dist. mkd. ¼ S BT.
A Fir 5" dia., bears S.78°W., 12 lks. dist. mkd. ¼ S BT.

Elliott State Forest Boundary Survey - L. Beyers and E. Lough - 1941 - (DCSO Field Book 120 Page 41

Failed to find ¼ S 15/16. Set 4x4 Cedar post "¼ 15 & 16"

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Jan. 27, 1971 - M 42-26

Set OSBF 1½" x 34" galv. iron pipe with 3" bronze cap, from which
20" Fir N.13°W., 12.9 ft. "RS 359"
24" Fir N.22½°E., 67.7 ft.
Yellow metal location poster on 25" Fir stump, S.30°W., 1.1 ft.
White painted cedar post N.15°E., 1.5 ft.
1941 Elliott survey post, N.53 ¾°W., 86.8 ft.

Jerry Estabrook - For: Oregon Dept. of Forestry - Feb. 2017 - M173-9

Found - A 1½" iron pipe with 3" brass cap mkd "¼ S16 S15 1970" PER M42-26.
A 20" Fir snag with visible scribe in face bears N.13°W., 12.9'.
A Rotten Fir stump with no visible marks bears N.22°30'E., 67.7'.
New BTs- A 17" Fir face scribed "E¼ S16 BT" with mag nail and washer stamped "LS2703" in bottom of face and with x-chop and YMLP at breast height bears S.13°W., 26.0' to a spike at side center.
A 12" Fir face scribed "E¼ S16 BT" with mag nail and washer stamped "LS2703" in bottom of face and with x-chop and YMLP at breast height bears S.72'W 26.2' to a spike at side center.
A 10" Fir face scribed "E¼ S16 BT" with mag nail and washer stamped "LS2703" in bottom of face and with x-chop and YMLP at breast height bears N.44°W., 29.5' to a spike at side center.

continued next page

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 38" Hemlock face scribed "E $\frac{1}{4}$ S16 BT" with mag nail and washer stamped "LS2703" in bottom of face and with x-chop and YMLP at breast height bears N.06°W., 8.3' to a spike at side center.
New BO - An orange carsonite post north 2.0'.