

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION C C for Secs. 9 and 10 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1939-40)

At a point 3.80 chs. West of cor. to Secs. 15 & 16, I set a post, 4 ft. long and 4" sq., 2 ft. in the ground for closing cor. to secs. 9 and 10 marked C C T22S R11W on N.; S10 on E.; and S9 on W. faces, with 4 notches on S. and 3 notches on E. edges, from which

A Fir stump 24" dia., bears N.64°E., 29 lks. dist. mkd. T22S R11W S10 BT.

No other trees in limits.

Built a mound of stone 1½ ft. high, 2 ft. base, 5 lks. S. of post.

A cliff of rock 4 ft. high bears North 53 lks. dist. mkd. S9 BO.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Jan. 27, 1971 - M 42-26

Set OSBF 1½" x 36" galv. iron pipe with 3" bronze cap, from which

22" Fir N.1°E., 46.9 ft. "RS 359"

15" Fir N.34°W., 61.0 ft. with yellow metal location poster.

4"x4"x72" white painted cedar post N.19°E., 3.7 ft.

Fd. & used on Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20216)