

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 400577

PRIMARY CORNER DESCRIPTION C C for Secs. 4 and 9 only (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1941-42)

At a point 4 chs. South of old cor to secs. 3, 4, 9 and 10, I set a post, 4 ft. long and 4" sq., for closing cor. to secs. 4 and 9, marked C C T22S R11W on E.; S4 on N.; and S9 on S. faces, with 5 notches on S. and 3 notches on E. sides, from which
A Fir 4" dia., bears S.16°W., 39 lks. dist. mkd. T22S R11W S9 BT.
A Fir 3" dia., bears N.63°W., 51 lks. dist. mkd. T22S R11W S4 BT.
An Alder 8" dia., bears S.57°E., 197 lks. dist. mkd. T22S R11W CC S4 & 9 BT.

Elliott State Forest Boundary Survey - L. Beyers and E. Lough - 1941 - (DCSO Field Book 120 Page 113-114)

Set a 4"x4"x3 ft. cedar post in mound of stone at a point agreeing with orig. notes of survey. At this point, found rotten wood in hole 1 ft. deep, from which a
22" Fir bears S.16°W., 38 lks.
18" Fir bears N.63°W., 51 lks.
12" Alder bears S.57°E., 197 lks.
Chopped into a 22" Fir 10" and found old blaze put on when tree was 4" dia. No scribes. Found 12" dead Alder which had previously been chopped out. No scribe marks.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - by Elbert Drive, Wit: Derald Timmons and Ron Witham - File Feb. 24, 1958 - C.S. File 42/340-2

Original post, now missing, found 4x4x48" white cedar post in stone mound, from which
4" Fir bears S.16°W., 39 lks.; now 26", uncovered burnt face, orig. axe work visible.
3" Fir bears N.63°W., 51 lks.; now 28" stump, face unexposed, dist. is 13.9 ft.
8" Alder bears S.57°E., 195 lks.; now missing.
Set 1½" x 36" galv. I.P. with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY T22S R11W CC S4 S9 S10 1957 RS 359", 33" in ground, in mound of stone, and from which a:
20" Fir bears S.52°W., 5.7 ft.; scribed T22S R11W S9 BT.
28" Fir stump (orig.) bears N.63°W., 13.9 ft.; scribed BT.
26" Fir bears S.86°E., 16.8 ft.; scribed RS 359.
(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 400577

PRIMARY CORNER DESCRIPTION C C for Secs. 4 and 9 (East side)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set 4"x4"x48" white painted cedar post 1.5 ft. North of pipe. OSBF metal location poster on 28" Fir stump BT.
Fd. OK, June 1975 by R.E. Stuntzner - M 57-54
Fd. OK, Nov. 1978 by T. Hoesly - M 74-65
Fd. & used on Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCS0 records Vol. 53 Page(s) 20221-2)