

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 400638

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 4 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Aug. 11, 1971 - M 44-34

-----  
(Established witness corner, N.00°44'E., 15.27 ft. from true corner)

Set OSBF I.P. with 3" bronze cap 36" in ground from which "X" on 3'4'5" boulder in stream bed, S.63°W., 72.9 ft. 6" (X BO)

8" Myrtle, in clump of 12, S.33½°W., 58.0 ft. (RS359) with yellow metal location poster.

White painted cedar post, North 1.5 ft.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Feb. 24, 1993 - C.S. File 64/39-16

-----  
Found - A 3" dia. OSBF brass cap on an iron pipe 18" below ground. Unable to read top of brass cap.  
5' x 2' x 1/2' high sandstone boulder, no "X" found, bearing and distance from 1971, fits boulder. (Rec. S.63°W., 72.9 ft.)

8" now 11" dia. Myrtle in cluster of Myrtles, center of NE trunk has a partially healed double blaze, scribing visible "X".

BC/IP West 1/4 cor for Sec. 3, bears N.0 3/4°E., 116.7 ft.

New Accessory:

Power pole bears N.6½°W., 297.6 ft.

Fd. & used on Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20219)

Found OK by H. Wilcox, Aug. 2002 - see LP 2003-0001 A&B