

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 3 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 5 Page(s) 1860)</p> <p>-----</p> <p>Set ¼ sec. post from which A Willow 5" dia., bears S.40°E., 17 lks. dist. A Willow 5" dia., bears S.45°W., 3 lks. dist.</p>
<p>Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: Mallery; Lewellyn; Gresham - Jan. 1964 - C.S. File 51/260 and M 27-28</p> <p>-----</p> <p>Set galv. I.P. with 3" bronze cap 48" under ground in open field, from which White painted cedar post S.0°44'W., 114.5 ft. in fence line on West edge Hakki Creek, yellow metal location poster. White painted cedar post N.41°30'E., 162.3 ft. in fence line on South side of driveway with yellow metal location poster.</p>
<p>Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Feb. 24, 1993 - C.S. File 64/39-15</p> <p>-----</p> <p>Found - A stong metal reading in hole is found S.83°W., 3.0 ft. from wooden post with nail. With shovel, top of cap is found in hole 2½ ft. below ground. Hole full of water. No post from 1964 is found. 7" now 10" dia. Alder scribed "X BT" bears N.73 3/4°E., 231.8 ft. (agrees w/BLM) 10" now 12" dia. Alder with a fully healed single blaze bears S.39°E., 169.7 ft. (agrees w/BLM) BC/IP witness cor. for ¼ sec. 4 bears S.0 3/4°W., 116.7 ft.</p> <p>New Accessory: Power pole bears N.13¼°W., 182.9 ft.</p>
<p>BLM Resurvey by John A. Farmer, Cadastral Surveyor, under Group #1421, surveyed Nov. 1987/Aug. 1994 - (DCSO Records, Vol. 51 Page 19287</p> <p>-----</p> <p>The ¼ sec. cor. of sec. 3 only on the E. bdy. of sec. 4, reestablished and recorded by Gibson, in 1963, and is accepted as the corner; monumented with an iron pipe, firmly set, buried 45 ins. below the surface of the ground, with brass cap mkd. (Cont. Next Page)</p>

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 400640

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

$\frac{1}{4}$   S 3 1963
from which new bearing trees An alder, 7 ins. diam., bears N. 73 3/4° E., 351 lks. dist., mkd. X BT. An alder, 10 ins. diam., bears S. 39½° E., 257 lks. dist., mkd. ¼ S3 BT.
Fd. & used on Dependent resurvey by Boyd W. Peterson, Cadastral Surveyor, & Richard Sanford, Surveying Technician, under Group #1644, surveyed April 1992/May 1996. (DCSO records Vol. 53 Page(s) 20219)
Found OK by H. Wilcox, Aug. 2002 - see LP 2003-0001 A&B