

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 404500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15 & 16 only, North

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1928)

Set a stone 12x10x6 ins., 8" in the ground for cor. to 15 & 16, marked with 4 notches on the S. and 3 notches on the E. edges, from which

- A Fir 8" dia., bears S.40°E., 90 lks. dist. mkd. T22S R11W S15 BT.
- A Maple 3" dia., bears S.24°W., 7 lks. dist. mkd. T22S R11W S16 BT.
- A Fir 4" dia., bears N.10°E., 54 lks. dist. mkd. T22S R11W S15 & 16 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Jan. 27, 1971 - M 42-26

Set Oreg. St. Bd. of Forestry 1½" x 10" galv. iron pipe with 3" bronze cap, 6" in concrete, in sandstone., from which
16" Fir S.5°W., 36.1 ft.
13" Fir S.37°E., 12.0 ft. "RS 359". Yellow metal location poster.
White painted cedar post, North 4.8 ft.