

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 431100

PRIMARY CORNER DESCRIPTION A.P. on So. bdy. Sec. 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1880)

This point falling on solid bed rock sloping to the S., I marked a cross (X) at exact cor. point for cor. to secs. 3 and 4, cut 3 notches on the E. and 3 notches on the W. of (X) cross, from which

- A Fir 10" dia., bears S.22½°E., 44 lks. dist. mkd. T23S R11W S3 BT.
- A dead Fir 40" dia., bears S.20°W., 40 lks. dist. mkd. T23S R11W S4 BT.
- A dead Fir 50" dia., bears N.33°E., 71 lks. dist. mkd. T23S R11W S3 & 4 BT.

GLO survey by Albert N. Gould, Deputy Surveyor, under Contract #762, dated July 12, 1905 - (DCSO records Vol. 5 Page(s) 1977)

Cor. of secs. 3 & 4 which is a X marked on smooth bed rock, which I marked A.P. witnessed as described by the Surveyor General, which said witnesses I marked A.P. BT.