

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1930)

Set a post, 3 ft. long and 3" sq., 2 ft. in the ground for ¼ sec. cor. marked ¼ S. on W. face, from which
A burnt Fir 50" dia., bears S.87°W., 192 lks. dist. mkd. ¼ S BT.
No other trees in limits and pits impracticable.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: Schulson and South - Nov. 1963 - C.S. File 51/260-7

Orig. post, now missing, from which a:
50" burnt Fir bears S.87°W., 192 lks.; now 50" rotted, burnt, 15 ft. high stub, orig. scribe S and more recent knife scribes BT.
Set 1½" x 36" galv. iron pipe with 3" bronze cap mkd. "Ore. St. Bd. of Forestry ¼ S15 S22 1963 RS 359", from which a:
34" Fir bears N.32°W., 21.6 ft. scribed ¼ S15 BT RS359.
24" Fir bears S.46½°W., 29.7 ft. scribed ¼ S22 BT.
Set 4x4x72" white painted cedar post 2 ft. South of corner pipe.
OSBF metal location poster on 14" Fir, N.79°W., 5.8 ft.