

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 10 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1928)

Set a post, 3 ft. long and 3" sq., 2 ft. in the ground for ¼ sec. cor. marked ¼ S. on N. face, from which
A Fir 12" dia., bears N.80°E., 74 lks. dist. mkd. ¼ S BT.
A Fir 8" dia., bears S.72°E., 75 lks. dist. mkd. ¼ S BT.

Elliott State Forest Boundary Survey - L. Beyers and E. Lough - 1941 - (DCSO Field Book 120 Page 89-90)

Found 30" Fir and chopped in 10" and uncovered part of scroll S \, from this BT, set cor. S.80°W., 74 lks. Set 4"x4"x3 ft. cedar post ¼ S10.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Crew: Drive; Timmons and Witham - July 11, 1958 - C.S. File 42/340-6

Original post, now missing, found 4x4x48" white painted cedar post in stone mound out of place, from which a:
8" Fir bears S.72°E., 75 lks.; now 33", face unexposed.
12" Fir bears N.80°E., 74 lks.; now 36", uncovered scribes ¼ S, remainder unexposed.
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "OREGON STATE BOARD OF FORESTRY ¼ S10 1958 RS359", 33" in ground, in mound of stone, and from which a
28" Fir bears S.4¼°W., 24.8 ft. scribed RS 359.
41" Fir bears N.57½°E., 79.8 ft. scribed ¼ S10 BT.
OSBF metal location poster on orig. 12" Fir BT.

Fd. OK, March 1986 by Lloyd Smith, OSBF - M 100-39