

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 5 Page(s) 1860)

Set ¼ sec. post, from which
 A Willow 8" dia., bears N.75°E., 117 lks. dist.
 A Maple 4" dia., bears S.34°W., 186 lks. dist.

Elliott State Forest Boundary Survey - L. Beyers and E. Lough - 1941 - (DCSO Field Book 120 Page 77)

At 39.50 chs., Set a 4"x4"x3 ft. cedar post for ¼ cor.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - by Elbert Driver - Wit: Derald Timmons; Ron Witham - Filed Feb. 24, 1958 - C.S. File 42/340-4 and M 9-34

No evidence of original corner found.
Set 1½" x 36" galv. iron pipe with 3" bronze cap marked "Oregon State Board of Forestry ¼ S3 S10 1958 RS 359", 33" in ground, in mound of stone, and from which a
 24" Fir bears S.52°W., 144.9 ft. scribed ¼ S10 bT.
 21" Maple clump S.41½°W., 101.0 ft. scribed RS 359.
Set 4"x4"x48" white painted cedar post, 1.5 ft. NW of pipe
OSBF metal location poster on 25" Fir stump S.66°W., 68.5 ft.

Fd. OK, May 1985, K. DeGroot - M 98-57 A&B
Fd. OK, March 1986, L. Smith - M 100-39

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Feb. 22, 1993 - C.S. File 64/39-12

Found - A 1958 3" dia. brass cap on a 2" O.D. Iron pipe, firmly set and protruding approx. 3" above ground. 4x4x48" white painted cedar post 1.5 ft. NW of corner monument, not found. BC is surrounded by remnants of a loose mound of stone.
 21" Maple clump, now a 42" DBH, 7 ft. tall Maple stump (partially fused multi trunk grown from common root crown) with a healed single blaze on the most northeasterly trunk, bears S.41½°W., 102.2 ft. to center of the common root crown (the center of the scribed trunk bears S.41½°W., 101.0 ft. as per rec.)

(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 440600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 3 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

24" Fir now a 30" DBH, 6 ft. tall Fir stump with a fully healed single blaze, bears S.52°W., 144.9 ft. (as per record)
25" Fir stump with an OSBF metal tag, now a burned and rotted Fir stump with no metal tag, bears S.66°W., 68.5 ft. (per record)
17" dia. 3 ft. tall broken Alder stump with the bark scribing "BT" visible, bears N.71½°W., 33.4 ft. dist. This tree is not of record.
New BT - Maple with four trunks growing from a common root crown, the most northerly trunk of which is 10" DBH and is scribed "¼ S10 CS BT", the center of the root crown of the Maple bears S.8 ¾°E., 98.5 ft. dist.
Monument is on steep northerly slope of a SW-NE running drainage. Monument is approx. 50 ft. above canyon floor.

BLM resurvey by John A. Farmer, Cadastral Surveyor, under Group #1421, surveyed Nov. 1987/Aug. 1994 (DCS0 Records, Vol. 51 Page 19287)

The ¼ sec. cor. of secs. 3 and 10, reestablished and recorded by Arnold G. Gibson, Registered Land Surveyor No. 359, for the Oregon State Board of Forestry in 1958, and is accepted as the corner; monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.

¼ $\frac{S\ 3}{S\ 10}$
1958
RS 359

from which bearing trees mkd. by Gibson
A fir, 30 ins. diam., bears S. 52° W., 220 lks. dist., with healed blaze.
A maple, 33 ins. diam., bears S. 41½° W., 153 lks. dist., with healed blaze.
and a new bearing tree
An alder, 15 ins. diam., bears N. 69½° W., 35 lks. dist., mkd. ¼ S3 BT.