TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 440640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Section 3

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Warren D. Hootman - May 13, 1972 - M 45-5

Set 1¼" Pipe for center of section.
No bearing trees marked.

Survey by Kristian DeGroot, LS #1941 - Baughman Tech. Co. - For: Dr. Clinton Faber - May 1985 - M 98-57 A&B

Set 5/8" x 30" Iron rod with a plastic survey cap mkd. "Baughman Tech. Serv.", from which
- A 12" Spruce bears N.29°E., 18.3 ft. scribed "C¼ S3 BT" with a brass washer "LS 1941" nailed in lower blaze.
- A 6" Spruce bears S.12½°E., 12.8 ft. scribed "C¼ S3 BT" with a brass washer "LS 1941" nailed in lower blaze.
- A 1" iron pipe bears S.57°48'43"E., 22.46 ft. as set by Hootman in 1972.

BLM Resurvey by John A. Farmer, Cadastral Surveyor, under Group #1421, surveyed Nov. 1987/Aug. 1994 - (DCSO Records, Vol. 51 page 19291)

The center ¼ sec. cor. of sec. 3, established and recorded by in 1985, and is accepted as the corner; monumented with an iron pin, 5/8 in. diam., firmly set flush with the ground, with plastic cap mkd. BAUGHMAN TECH SERV.
At the corner point
Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T22S R11W
C¼ S 3
1987

from which bearing trees mkd. by DeGroot
- A spruce, 13 ins. diam., bears N. 23° E., 28 lks. dist., with scribe marks C¼ S3 BT visible on partially healed blaze.
- A spruce, 7 ins. diam., bears S. 19° E., 19½ lks. dist., with illegible scribe marks visible on partially healed blaze.

Deposit a white "DEEP-1" magnetic marker and iron pin at the base of the stainless steel post.

Found ok by K.DeGroot - 4/1998 - M128-57