

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1918-19)

Set a post, 3 ft. long and 3" sq., 2 ft. in the ground for ¼ sec. cor. mkd. ¼ S. on W. face, from which
A Fir 6" dia., bears S.65°E., 35 lks. dist. mkd. ¼ S BT.
A Fir 8" dia., bears S.23°W., 83 lks. dist. mkd. ¼ S BT.

Elliott State Forest Boundary Survey - L. Beyers and E. Lough - 1941 - (DCSO Field Book #120 Page 34)

I found some stones which appeared they may have been piled about a stake. From this point a:
32" Fir bears S.24°W., 81 lks. dist.
28" Fir bears S.62°W., 35 lks. dist.
There are very slight indications on each tree of old grown over blazes. Since these trees are the only ones near and so nearly correspond with notes for the original BTs:
I set a Cedar post for ¼ cor. bet. 14 and 15 at this point.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: Lloyd Smith and David Brown - Aut. 10, 1970 C.S. File 55/154-6

Found original post, missing. Found cedar post 1 ft. SW., from which a:
6" Fir bears S.65°E., 35 lks., now 38" exposed scribes S1
8" Fir bears S.23°W., 83 lks., now 34" snag 50 ft. tall, center 18", rotted out.
Restoration by Elliott State Forest Survey, 1941:
Cedar post, (see above)
Set 1½" x 36" galv. I.P. with 3" bronze cap mkd. "Ore. St. Bd. of Forestry ¼ S15 S14 1970 RS 359", 34" in ground, Elliott post alongside, in mound of rock, and from which a:
11" Fir bears S.38½°W., 27.7 ft. to face, scribed ¼ S15 BT RS 359.
3' x 3' point of sandstone bedrock bears S.77½°E., 7.9 ft. to face, chiseled 6" X BO.
Set 4"x4"x72" white painted cedar post 3.8 ft. NW. of corner pipe.
OSBF metal location poster on 38" orig. Fir BT, S.65°E., 21.6 ft.