

PRIMARY CORNER DESCRIPTION E. 1/4 Cor for Sec. 10 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by W.H. Byars, Deputy Surveyor, under Contract #202, dated March 11, 1875, - (DCSO records Vol. 5 Page(s) 1861)</p> <p>-----</p> <p>Set a stone, boulder, 20x10x10 for the ¼ sec. cor. No trees near.</p>
<p>GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1974)</p> <p>-----</p> <p>The old ¼ sec. cor. which is a stone 10x10x5 ins. above ground marked ¼ on W. side, from which A Maple 7" dia., bears S.2°W., 267 lks. dist. which I mark ¼ S BT. No other trees in limits.</p>
<p>Elliott State Forest Boundary Survey - L. Beyers and E. Lough - 1941 - (DCSO Field Book 120 Page 46) and (DCSO records, Field Book 122 page 9)</p> <p>-----</p> <p>Reset E. ¼ cor. Sec. 10, Set post - failed to find old cor.</p>
<p>Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - witnessed by Hollingsworth; Bagger, and Baughn - June 1963 - C.S. File 51/260 and M 26-25</p> <p>-----</p> <p>¼ corner reestablished. Set 1½" x 36" galv. iron pipe with 3" bronze cap., from which 26" Fir S.10°W., 53.8 ft. 14" Maple N.77°W., 26.7 ft. with yellow metal location poster. White painted cedar post NW 1.5 ft. Elliott Survey Post 1941, East 20.0 ft.</p>
<p> </p>