

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 504500

PRIMARY CORNER DESCRIPTION Sec. cor. for 14 and 15 only, (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1908)

-----  
(4 chs. East of corner for 10 & 11 only)  
Set a stone 16x12x10 ins., in mound of stone 1½ ft. high with 2 ft. base for cor. to secs. 14 and 15 with 4 notches on S. and 2 notches on E. faces. No trees in limits. Too rocky to set a stone in ground.

-----  
Elliott State Forest Boundary Survey - L. Beyers and E. Lough 1941 - (DCSO Field Book 120 Page 3 & 4)

-----  
Found a stone set in a mound of stone on top of ridge as described in field notes. Notches have weathered off of stone. No witness trees.  
Blazed a Fir 14" dia., which bears S.50°W., 18 lks. dist. mkd a ◇ in center of blaze.

-----  
Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - witnessed by Schulson and South - Nov. 1963 - C.S. File 51/260-6

-----  
Orig. stone 16x12x10" in stone mound, found in place on top of ridge, notches weathered and indistinct, 3.93 chs. E. of Sec. cor. 10 & 11.  
Restoration by 1941 Elliott Survey:  
14" Fir bears S.55°W., 18 lks.; now 20", blaze grown over, uprooted to North.  
Set 4x4x72" white painted cedar post 2.0 ft. SW of corner stone from which  
17" Fir bears S.37½°W., 20.0 ft. scribed T22S R11W S15 BT.  
14" Fir bears S.82½°E., 48.7 ft. scribed T22S R11W S14 BT RS359.

-----  
Section cor. Fd., 2" X on orig. stone, 2 old BTs. - OSBF, 1971 - M 42-26