

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1920)

Set a stone 20x12x8 ins., 15" in the ground marked ¼ on N. face for ¼ sec. cor., from which
A Cedar stub 24" dia., bears N.10°W., 90 lks. dist. mkd. ¼ S BT.
A Fir stub 24" dia., bears S.68°W., 190 lks. dist. mkd. ¼ S BT.

Elliott State Forest Boundary Survey - L. Beyers and E. Lough - 1941 - (DCSO Field Book 120 Page 15 & 16)

Found stone 20"x10"x8", buried 15" in ground with a 4 marked on North face. BTs have burned or decayed. Found one Cedar root in ground at location described for Cedar stub.
Set a 2"x2"x2 ft. Cedar stake by stone, marked ¼ S14/23.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: Schulson and South - Nov. 1963 - C.S. File 51/260-4

Original stone 20"x12"x8", found in place, ¼ on N. side, from which:
24" Cedar stub bears N.10°W., 90 lks.; missing. This area heavily burned since original survey.
24" Fir stub bears S.68°W., 190 lks.; missing. Burned out
Restoration by 1941 Elliott survey:
2"x2" cedar stake, found on West side of corner stone.
Set 4x4x72" white painted cedar post 1.0 ft. W. of corner stone, in mound of rock and from which:
30" Fir bears S.59°E., 32.5 ft.; scribed ¼ S23 BT RS 359
Rock bluff 8 ft. x 10 ft. x 4 ft. high, facing West, bears S.8°E., 38.4 ft., scribed X B0.