

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 542600

PRIMARY CORNER DESCRIPTION North 1/4 Cor. for Sec. 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1903)

-----  
A stone in place 10x5x1 ft. above ground which I mark with a cross "X" at exact cor. point for ¼ sec. cor. with ¼ N. of cross.

No trees in limits

A stone 24x24x18 ins. above ground bears South 14 lks. dist. marked ¼ B0.

Build a mound of earth 1½ ft. high 3½ ft. base alongside.

Pits impracticable.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - wit: Hollingsworth; Bagger; Baughn - June 1963 - C.S. File 51/260-1 and M 26-25

-----  
Original stone 10'x5'x1' above ground, found in place but composed of several smaller segments to make the above size, X and musical ¼ note visible on segment of stone, from which

Stone 24x14x18" above ground bears South 14 lks.; found in place, split in half and badly sluffed, chisel marks visible.

Scribed a new ¼ on North side of stone, from which a

34" Fir bears S.48½°E., 48.9 ft. scribed ¼ S11 BT.

26" Fir bears N.31°E., 19.5 ft. scribed RS 359.

OSBF metal location poster on 26" Fir BT.

Set 4'x4"x72" white painted cedar post 1.5 ft. SE of corner stone.