

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION C C for Secs. 35 and 36 (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1918)

I set a stone 18x12x6 ins., 12" in ground for cor. to secs. 35 and 36, mkd. C C with 1 notch on E. and 5 notches on W. edges, from which

A burnt Fir 40" dia., bears N.49°E. 84 lks. dist. mkd. T22S R11W S36 BT.

A burnt Fir 40" dia., bears N.8°W., 112 lks. dist. mkd. T22S R11W S35 BT.

An Alder 5" dia., bears S.45°W., 15 lks. dist. mkd. T22S R11W S35 & 36 CC BT.

GLO survey by Albert N. Gould, Deputy Surveyor, under Contract #762, dated July 12, 1905 - (DCSO records Vol. 5 Page(s) 1976)

Closing cor. of secs. 35 and 36 which is a sandstone, 18x12x6 ins., marked and witnessed as described by the surveyor general.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Jan. 21, 1972 - C.S. File 55/265 and M 45-3

Set OSBF galv. iron pipe 35" in ground, from which
34" Fir N.88°W., 93.5 ft. with yellow metal location poster.

42" Fir N.48°E., 39.3 ft. (RS 359)

Set 4" x 4" x 72" white painted cedar post South 1.6 ft.