

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor for Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1917)

Set a post 3 ft. long and 3" sq., 2 ft. in the ground for ¼ sec. cor. marked ¼ S. on W. face, from which
A Fir 20" dia., bears N.56°W., 22 lks. dist. mkd. ¼ S BT
An Alder 10" dia., bears N.78°E., 13 lks. dist. mkd. ¼ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Charles Cook, Engineer - May 30, 1972 - C.S. File 55/233-10

Original post, missing, from which a:
20" Fir bears N.56°W., 22 lks.; now 27" freshly cut stump, scribes 1/ visible.
10" Alder bears N.78°E., 13 lks.; missing.
Set 1½" x 36" galv. iron pipe with 3" bronze cap mkd. "OREGON STATE BOARD OF FORESTRY ¼ S35 S36 1971 RS 359", 34" in ground, in side draw, course N.30°W., and from which a:
4 ft. wide rock draw, course N.30°W., bears S.33½°E., 8.0 ft.; chiseled 6" X BO.
4 ft. high x 20 ft. rock face bears N.54¼°W., 44.6 ft.; chiseled 6" X BO.
Set 4" x 4" x 72" white painted cedar post 4.3 ft., S.84°E., of corner pipe.
OSBF metal location poster on 24" Fir stump, orig. BT, N.56°W., 13.4 ft.
Also poster on 4 ft. high x 20 ft. rock face, N.54¼°W., 44.6 ft.