

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1906-07)

I set a sandstone 12x10x5 ins., 8" in the ground for cor. to secs. 11, 12, 13 and 14, with 4 notches on S. and 1 notch on E. edges, from which
A Fir 8" dia., bears N.15°E., 36 lks. dist. mkd. T22S R11W S12 BT.
A Fir 12" dia., bears S.29°E., 100 lks. dist. mkd. T22S R11W S13 BT.
An Alder 12" dia., bears S.80°W., 60 lks. dist. mkd. T22S R11W S14 BT.
An Alder 24" dia., bears N.52°W., 73 lks. dist. mkd. T22S R11W S11 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit: Shore; Lewellyn; South and McCleve - April 1961 - C.S. File 42/403-18

Orig. stone 12"x10"x5", missing. Area now bare rock, from which
8" Fir bears N.15°E., 36 lks.; now 16", orig. face overgrown. Cut through orig. face also overgrown.
12" Fir bears S.29°E., 100 lks.; now 38", faces overgrown, bearing S.39°E.
12" Alder bears S.80°W., 60 lks.; now missing, point falls in slide area.
24" Alder bears N.52°W., 73 lks.; now missing, point covered by slide.
Bottom of gulch, course NE, bears West 1 ch.; now in place
Bottom of gulch, course NE, bears North 2.16 chs.; now in place.
Scribed X on bedrock for corner point, from which
13" Cedar bears S.69½°W., 32 ft.; scribed T22S R11W S14 BT
10" Cedar bears N.33½°W., 42.9 ft. scribed T22S R11W S11 BT RS 359.
30 ft. x 5 ft. high rock ledge bears S.45°E., 11.4 ft. scribed X B0.
OSBF metal location poster on 10" Cedar BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Feb. 10, 1977 - C.S. File 58/31

Found orig. 12"x10"x5" stone, missing, X in place on bare rock, from which
8" Fir bears N.15°E., 36 lks.; now 22" stump in place, face closed. (Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

12" Fir bears S.29°E., 100 lks.; now 50" stump in place, faces closed bearing S.39°E.

12" Alder bears S.80°W., 60 lks.; missing, point falls in slide out draw.

24" Alder bears N.52°W., 73 lks.; missing, point falls in slide area.

Restoration by Gibson, 1961:

X on bedrock for corner point, in place., from which a 13" Cedar bears S.69½°W., 32.0 ft., now 17" stump in place, scribes T22S R11W visible.

10" Cedar bears N.33½°W., 42.9 ft. missing, point falls in slide out draw.

30 ft. x 5 ft. rock ledge bears S.45°E., 11.4 ft.; in place, scribes B0 X visible.

Set 3" bronze cap mkd. "Oregon State Board of Forestry T22S R11W S11 S12 S14 S13 1977 RS 359", 3" in ground, in concrete in bedrock, in place of X and from which a

Orig. 50" Fir stump bears S.39°E., 66.0 ft. to face, scribed RS 359.