

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1906)

Set a stone 12x9x7 ins., 8" in the ground for ¼ sec. cor. marked ¼ on W. side, from which
A Fir 4" dia., bears S.75°E., 12 lks. dist. mkd. ¼ S BT
A Willow 3" dia., bears S.42°W., 5 lks. dist. mkd. ¼ S BT

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Wit. by Hollingsworth; Bagger and Baughn - June 1963 - C.S. File 51/260 and M 26-25

Set G.I.P. 30" in ground, from which
22" Fir N.44°E., 9.6 ft.
24" Fir S.14°W., 28.4 ft.
Yellow metal location poster on 12" Madrone S.30½°E., 8.2 ft.
Elliott survey post, 1941, S.80°E., 82.0 ft.
White painted cedar post NE. 1.5 ft.