

PRIMARY CORNER DESCRIPTION A.P. S. bdy. Sec. 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1883)

Set a stone 20x12x6 ins., 14" in the ground at a point about 250 ft. below top of mounain for cor. to secs. 1 and 2, marked with 1 notch on the E. and 5 notches on the W. edges, from which,

- An Alder 4" dia., bears S.81°W., 68 lks. dist. mkd. T23S R11W S2 BT.
- A dead Fir 50" dia., bears S.77°E., 72 lks. dist. mkd. T23S R11W S1 BT.
- A dead Fir 50" dia., bears N.67°W., 40 lks. dist. mkd. T23S R11W S1 & 2 BT.

GLO survey by Albert N. Gould, Deputy Surveyor, under Contract #762, dated July 12, 1905 - (DCSO records Vol. 5 Page(s) 1976)

Cor. of secs. 1 & 2 which is a stone 20x12x6 ins., which I marked A.P. witnessed as desribed by the Surveyor General, which said witnesses I marked A.P. BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Jan. 21, 1972 - C.S. File 55/265 and M 45-3

Original stone, missing, from which a:
50" dead Fir bears N.67°W., 40 lks.; now 27" x 10 ft. high rotted Fir stub, in place.
50" dead Fir, bears S.77°E., 72 lks.; now in place, scribes R11W remaining.
4" Alder bears S.81°W., 68 lks.; missing.
Set 1½" x 36" galv. iron pipe with 3" bronze cap mkd: "Oregon State Board of Forestry S2 T23S R11W AP 1971 RS 359", 35" in ground, and from which a:
35" Fir bears S.70¼°W., 19.6 ft. to face; scribed T23S R11W S2 AP BT.
28" Fir bears S.57 3/4°E., 27.1 ft. to face; scribed T23S R11W S2 AP BT RS 359.
Set 4" x 4" x 72" white painted cedar post 3.5 ft., S.76°W. of corner pipe.
OSFD metal location poster on 35" Fir BT, S.70¼°W., 19.6 ft.