

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1916)

A Fir 4" dia., which I marked $\frac{1}{4}$ S. on N. side for $\frac{1}{4}$ sec. cor. from which

A Fir 10" dia., bears N.50°W., 12 lks. dist. mkd. $\frac{1}{4}$ S BT.

A burnt Fir 50" dia., bears S.87°E., 18 lks. dist. mkd. $\frac{1}{4}$ S BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Oct. 1971 - C.S. File 55/233-9

Orig. 4" Fir, now rotted Fir root system, in place, from which

10" Fir bears N.50°W., 12 lks.; now 32", face grown over N.30°W.

50" burnt Fir bears S.87°E., 18 lks.; now, in place, scribes 1/ visible in rotted face.

Set I.P. with 3" bronze cap mkd: "Ore. St. Bd. of Forestry $\frac{1}{4}$ S25 S 36 1971 RS 359", 34" in ground and from which a:

22" Fir bears N.3 $\frac{1}{2}$ °W., 19.9 ft. to face; scribed $\frac{1}{4}$ S25 BT.

22" Fir bears S.48°W., 13.9 ft. to face; scribed $\frac{1}{4}$ S36 BT RS 359.

Set 4"x4"x72" white painted cedar post 2.1 ft. S.71°W. of corner pipe.

OSBF metal location poster on 22" Fir BT, N.3 $\frac{1}{2}$ °W.