

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 663100

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 2 only, T23-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Albert N. Gould, Deputy Surveyor, under Contract #762, dated July 12, 1905 - (DCSO records C.S. File 62/35-15 D)

At a point 16.52 chs. West of SE cor. of T22-11, I set a Fir limb post, 3 ft. long, 4' sq., 24" in the ground, for closing cor. of secs. 1 and 2, marked CC T23S R11W on S.; and S1 on E.; and S2 on W. faces, with 1 groove on E. and 5 grooves on W. edges; from which

An Alder 12" dia., bears S.40°E., 58 lks. dist. mkd. T23S R11W S1 BT.

An Alder 15" dia., bears S.83°W., 57 lks. dist. mkd. T23S R11W S2 BT.

Survey by Arnold G. Gibson - For: Oregon State Board of Forestry - Charles Cook, Engineer - Jan. 21, 1972 - C.S. File 55/265 and M 45-3

Set 1½" x 12" OSBF iron pipe with 3" bronze cap 6" in concrete 12' x 7' high sandstone bluff in stream bed, course N.45°W., S.27°E., 65.0 ft., with 6" X BO.

2' x 3' high sandstone face S.76½°W., 34.1 ft., 6" X BO.

30' x 10' high sandstone face S.05½°W., 39.8 ft. with yellow metal location poster.