

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1884 and 1893)

(Page 1884)

Set a temp Tp. cor. for the SE. cor. to T22S R11W.

Page 1893)

I set a post 4½ ft. long, 4" sq., 24" in the ground for the SE. cor. to Tp. 22 S., R. 11 W. marked T22S S36 on N.; R10W S31 on E.; T23S S1 on S. and R11W on W. faces, with 6 notches on N. and W. sides, from which,

An Alder 6" dia., bears N.85½°E., 66 lks. dist. mkd. T22S R10W S31 BT.

A burnt Fir 50" dia., bears N.59°W., 60 lks. dist. mkd. T22S R11W S36 BT.

An Alder 4" dia., bears S.53°E., 32 lks. dist. mkd. T23S R11W S1 BT.

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 4 Page(s) 1765)

Intersect the cor. to T22S Rs. 10 & 11 W. which is a post 4" sq., firmly set 24" above ground marked T22S S36 on N.; R10W S31 on E.; T23S S1 on S.; and R11W on W. with 6 notches on N. and W. faces, from which,

An Alder 6" dia., bears N.85°30'E., 66 lks. dist. mkd. T22S R10W S31 BT.

A burnt Fir 50" dia., bears S.59°W., 60 lks. dist. mkd. T23S R11W S1 BT.

An Alder 10" dia., bears N.41°W., 36 lks. dist. mkd. T22S R11W S36 BT.

GLO retracement survey by Albert N. Gould, Deputy Surveyor, under Contract #762, dated July 12, 1905 - (DCSO records Vol. 5 Page(s) 1976)

The SE. cor. of T22S R11W, which is a post, 12" high firmly set marked and witnessed as described by the Surveyor General.

Survey by Arnold Gibson - For: Oregon State Board of Forestry Charles Cook, Engineer - Jan. 21, 1972 - C.S. File 55/265; M 45-3

Set 1½" x 36" Iron pipe with 3" bronze cap, 34" in ground, from which,

(Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36 (SE Tsp. Cor.)

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

36" Fir N.22½°W., 59.6 ft. with yellow metal location poster, RS 359.
21" Fir N.63°W., 79.7 ft.
Set 4" x 4" x 72" white painted cedar post S.25°E., 2.0 ft.

James M. McIntosh, Oregon Dept. of Forestry - Witness: Ralph C. Hall - 7/2011 - C.S. File 65/72-30

Found - Orig Whipple, 1894, No evidence of orig corner fd. REESTABLISHMENT by Gibson, 1972: OSBF 1½"x36" galv. iron pipe with 3" bronze cap (fd pulled out of the ground and lying downhill)
36" Fir N.22½°W., 59.60 ft.; now 47" in place, face closed, yellow metal location poster.
21" Fir N.63°W 79.70 ft.; now 21"x2 ft. high rotted stump in place, partial scribes visible.
4"x4"x72" White Painted Cedar Post S.25°E., 2.0 ft.; missing.
Restored- Reset 1971 OSBF iron pipe with bronze cap 36" in ground from Gibson's 1971 BT's from which a:
44" Fir S.82°E., 109.00 ft. to aluminum nail in BT face scribed (T22SR10WS31 BT) bearing tree tag.
Carsonite witness post S.20°E., 5.70 ft. to base.
Carsonite witness post N.62°W., 9.90 ft. to base.
4"x4"x72" White Painted Cedar Post N.83°E., 2.80 ft. to base.
Magnetic variation set at 19° East.