

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 36 only

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1893)

 Set a stone 20x14x10 ins., 15" in ground for ¼ sec. cor. marked ¼ on W. face, from which
 A Fir 5" dia., bears N.87°W., 11 lks. dist. mkd. ¼ S BT.
 A burnt Fir 40" dia., bears N.81°E., 32 lks. dist. mkd. ¼ S BT.

Survey by Arnold Gibson - For: Oregon State Board of Forestry - Charles Cook, Engineer - Oct. 12, 1971 - C.S. 55/233-11

 Orig. stone 20x14x10" missing, from which a:
 5" Fir bears N.87°W., 11 lks. missing.
 40" burnt Fir bears N.81°E., 32 lks, in place, scribes ¼ S BT visible.
 Set 1½" x 36" I.P. with 3" bronze cap mkd: "Ore.St.Bd.of Forestry 1/4 S36 1971 RS 359", 34" in ground, from which:
 39" Fir bears N.53°W., 31.0 ft. to face, scribed ¼ S36.
 32" Fir bears S.54½°W., 86.8 ft. to face, scribed ¼ S36 BT.
 Set 4" x 4" x 72" white painted cedar post 1.2 ft. N.55°W. of corner pipe. OSFD metal location poster on 32" Fir BT.

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - March 3, 1992 - C.S. File 64/24-8

 Found - 3" OSBF brass cap on an iron pipe, found 5" below ground.
 Orig. NE BT is gone.
 39" now 36" dia. 1½ ft. high D.Fir stump with a fully healed single blaze, bears N.53°W., 31.7 ft. (Rec. N.53°W. 31.0 ft. dist. is a face measurement)
 32" now 36" dia. 5 ft. high D.Fir stump with a fully healed single blaze, bears S.54½°W., 87.8 ft. (Rec. S.54½°W., 86.8 ft. dist. is a face measurement)
 New BTs -30" dia. 4 ft. high D.Fir stump with boat spike through BT tag set on top of stump near center. Spike stamped "BO 1". Spike bears N.34°E., 23.0 ft.
 32" dia. 5 ft. high D.Fir stump with boat spike through BT tag set on top of stump near center. Spike stamped "BO 2". Spike bears S.74°E., 32.0 ft.