

PRIMARY CORNER DESCRIPTION E. Sec. cor. for 1 & 12 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #612, dated April 28, 1893 (DCSO records Vol. 5 Page(s) 1885-86)

Set a stone 16x12x7 ins., 10" in the ground for cor. to secs. 1, 6, 7 and 12, with 1 notch on N. and 5 notches on S. edges, from which,

A Fir 10" dia., bears N.32°15'E., 102 lks. dist. mkd. T22S R10W S6 BT.

A Fir 24" dia., bears S.18°15'E., 55 lks. dist. mkd. T22S R10W S7 BT.

A Fir 34" dia., bears S.6°50'W., 106 lks. dist. mkd. T22S R11W S12 BT.

A Fir 12" dia., bears N.13°W., 66 lks. dist. mkd. T22S R11W S1 BT.

Point is about 500 ft. above river bottom

GLO survey by Aurelius Todd, Deputy Surveyor, under Contract #629, dated April 24, 1894 - (DCSO records Vol. 5 Page(s) 1805-06)

Cor. to Secs. 1 & 12, which I find a stone 12x7x6 ins. above ground firmly set for cor. to secs. 1, 6, 7 & 12, marked with 1 notch on N. and 5 notches on S. edges, from which,

A Fir 14" dia., bears N.29°E., 41 lks. dist. mkd. T22S R10W S6 BT.

A Fir 24" dia., bears S.32°E., 48 lks. dist. mkd. T22S R10W S7 BT.

An Alder 4" dia., bears S.20½°W., 57 lks. dist. mkd. T22S R11W S12 BT.

A Fir 24" dia., bears N.73°W., 26 lks. dist. mkd. T22S 11W S1 BT.

I destroy all marks at this cor. relating to secs. 6 and 7.

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - P. Earle; J. Cook; K. Cheney, crew - June 24, 1976 - C.S. File 59/15-22

Found - A stone 16"x12"x7" with 1 notch on northerly edge and 5 notches on southerly edge. "X" chiseled on top. Stone located at the base of a small slide area.

A Fir 12" now 29", bears N.18°W., 45.6 ft. (Rec. N.13°W., 43.6 ft.) I partially open blaze and find scribing "S1"

A Fir 36" now a 55' windfall, badly rotted, bears S.8°W., 72.0 ft. approx. (Rec. S.6°50'W., 70.0 ft.) Tree scribed "R11W". (Cont. Next Page)

TOWNSHIP 22 RANGE 11 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION E. sec. cor. for 1 & 12 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set Brass cap at cor. stamped:
Douglas County Surveyors Office
T 22 S
R S 1 | S 6 R
11 S 12 | 10
W 1976 W

Set original corner stone on southerly side of cap and place witness sign and fence post on East side of cap.
New BTs -A D.Fir 10" bears S.58½°W., 10.7 ft. double blazed and scribed T22S R11W S12 CS BT.
Original 12" Fir bears N.13°W., 43.6 ft.

Fd. OK, Aug. 1976 by G. Baughman - M 65-12